

IES INDOOR REPORT
PHOTOMETRIC FILENAME : 2S-04-MU-MD-35-UNV-XX-X.IES

ZONAL LUMEN SUMMARY


Zone	Lumens	%Lamp	%Fixt
0-20	441.95	N.A.	7.10
0-30	914.91	N.A.	14.80
0-40	1456.46	N.A.	23.50
0-60	2453.77	N.A.	39.70
0-80	2992.88	N.A.	48.40
0-90	3047.66	N.A.	49.30
10-90	2931.23	N.A.	47.40
20-40	1014.51	N.A.	16.40
20-50	1548.88	N.A.	25.00
40-70	1340.44	N.A.	21.70
60-80	539.11	N.A.	8.70
70-80	195.98	N.A.	3.20
80-90	54.78	N.A.	0.90
90-110	144.13	N.A.	2.30
90-120	471.66	N.A.	7.60
90-130	994.71	N.A.	16.10
90-150	2210.39	N.A.	35.70
90-180	3139.6	N.A.	50.70
110-180	2995.47	N.A.	48.40
0-180	6187.26	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	116.43
10-20	325.53
20-30	472.96
30-40	541.55
40-50	534.37
50-60	462.93
60-70	343.13
70-80	195.98
80-90	54.78
90-100	21.94
100-110	122.19
110-120	327.53
120-130	523.05
130-140	616.83
140-150	598.84
150-160	493.34
160-170	323.38
170-180	112.49

POLAR GRAPH



Maximum Candela = 1245 Located At Horizontal Angle = 90, Vertical Angle = 2.5

- # 1 - Vertical Plane Through Horizontal Angles (0 - 180)
- # 2 - Vertical Plane Through Horizontal Angles (90 - 270)
- # 3 - Vertical Plane Through Horizontal Angles (45 - 225)
- # 4 - Horizontal Cone Through Vertical Angle (0)